

COLD PLUNGE CHILLER

Cool water temperature
down to **2°C**



ICE BATH CHILLER TECHNICAL HIGHLIGHTS

Horse Power	0.8 HP		1.0 HP	
Power Supply	100-127V	220-240V	100-127V	220-240V
	60Hz	50/60Hz	60Hz	50/60Hz
Input power	890W	880W	976W	1003W
Compressor power	660W	650W	755W	788W
Coling capacity	2105W	2000W	2440W	2395W
Cooling function	Yes			
Water temperature	3-42°C adjustable			
Water flow	16-20 L/min			
Water pump power	88W			
Water filter	Installed External			
Remote control	With Wi-Fi for Smart Living			
Swivel Casters (Transport Wheels)	Yes			
Carry handle	Yes			
Quick Coupler House Connection	Yes			
Power Cord with Leakage Protection Switch	Yes			
Net Weight	35KG		38KG	
Product Dimension	51*30.5*52.5 cm		54.5*33.2*50 cm	
Water Volume&Cooling Time(From 23 to 5°C Based on ambient temperature 28°C For your reference)	50L≤0.8H	50L≤1.2H	200L≤2.8H	200L≤3.1H
	100L≤1.7H	100L≤2.1H	300L≤4.3H	300L≤4.7H
	200L≤3.9H	200L≥4.2H	400L≤5.7H	400L≤6.2H
			500L≤6.5H	500L≤6.9H
Main Features	Advanced Design with Low Noise.			
	Water and Electricity Separating System.			
	24V Brushless DC Water Pump.			
	Equipped with Swivel Casters (Transport Wheels), Unlimited Location, Flexible and Convenient.			
	Easy Installation with Quick Coupler Hose Connection.			
	Equipped with Wi-Fi for Smart Life Control, Making Your Life Smarter and More Convenient.			
	Outstanding Value and Premium Quality.			